

Key Features:

- + 4.0 megapixel progressive scan CMOS
- + 2688 x 1520 resolution
- + 4 mm fixed lens offers horizontal FOV of 94°
- + Up to 100' white light distance
- + IllumiNite low light 0.0014 lux
- + H.265+ compression
- + Video analytics
- + IP66 weather-rated with -22°F – 140°F operating temperatures
- + ONVIF (Profile S, Profile G)
- + Micro SD card slot supports up to 128GB (Memory card sold separately)
- + Free Alibi Witness iOS/Android mobile app



4.0 Megapixel



4MP ILLUMINITE 100' WHITE LIGHT H.265+ IP TURRET CAMERA

IllumiNite with white light LED technology and Starlight chipset for clear, bright low light and nighttime images

Enjoy detailed color video images 24/7/365 with the Alibi 4.0 megapixel IllumiNite 100' white light IP turret camera.

This turret camera features a 4.0 MP high-performance CMOS and an active imaging pixel array of 2688 (H) x 1520 (V) that produces superior high definition video images.

This IP turret camera features a Starlight chipset with a super low light LUX rating, to capture color video in extreme low light conditions.

H.265+ video compression technology enables faster, more fluid remote viewing, and provides the ability to view more channels remotely. With H.265+ compression, you can store more information using less storage space. This camera also supports H.265, H.264+ and H.264.

The camera's 4 mm fixed lens covers a wide area with a horizontal FOV of 94°.

This IP turret camera is also equipped with advanced video analytics to help protect people and property more effectively, including Line Crossing, Intrusion Detection, Face Detection and more.

This IP camera also comes with flexible storage solutions. Its built-in micro SD/SDHC/SDXC slot (card not included), enables local storage up to 128GB.

This turret security camera is able to capture crisp images in any lighting conditions with 120 dB true Wide Dynamic Range (WDR) and 3D Digital Noise Reduction (3D-DNR), for superior 24/7 surveillance.

With an IP66 weather-rated metal enclosure, this IP turret camera has an operating temperature rating of -22° to 140°F and is protected from elements such as dust, sand and rain, making it an ideal outdoor security solution.

What's Included:

- + (1) 4.0 MP IP turret security camera
- + (1) Mounting template
- + (1) Mounting hardware
- + (1) Quick start guide



SPECIFICATIONS

Imager Type	Progressive Scan CMOS
Imager Size (in)	1/1.8
Color	Yes
Camera Resolution (px)	2688 x 1520 @ 30 fps
Megapixel	4.0
Day/Night Function	Yes
Digital Noise Reduction (DNR)	3D DNR
Dynamic Range (dB)	120
Electronic Shutter	1/3s - 1/100,000s
IR Array Range (ft)	100
Lux (Color)	0.0014 (0.0 with light)
AGC Control	Selectable
Wide Dynamic	Yes
FOV (degrees)	94
Focus	Fixed
Lens Mount	M14
Focal Length (mm)	4
Audio	Yes
Audio Compression	G.711/G.722.1/G.726/MP2L2
Audio Streaming	One-Way
Built in Mic	Yes
Ethernet Interface	RJ-45
Ethernet Ports	1
Ethernet Speed	10/100
Protocols	TCP/IP, HTTP, HTTPS, DHCP, UDP, RTP, RTSP and more
Remote Configuration	Yes
Remote Viewable	Yes
Bit Rate	32Kbps - 16Mbps
Compression Type	H.265+, H.265, H.264+, H.264, MJPEG
Email Notification	Yes
Event Log	Yes
Event Notification	Yes
Privacy Video Block	Yes
SD Card Reader	Yes
Storage Capacity (GB)	Up to 128 (micro SD card not included)
Video Analytics Capable	Yes
Dimensions	5.4" x 4.9"
Pan Angle	0°-360°
Tilt Angle	0° - 75°

Rotate Angle	0°-360°
Card Reader Type	Micro SD card, SDHC, SDXC
Construction	Plastic and Metal Alloy
Operating Humidity	0% - 95% (non-condensing)
Operating Temperature (F)	-22° - 140°
Product Color	White
Outdoor	Yes
Ingress Protection	IP66
Vandal-proof	IK10
Weight (lb)	1.3
PoE	802.3af
Power (w)	12 Vdc., Max: 6 W; PoE: (802.3af.), Max: 7.5 W
Volts DC	12
Mobile App	iOS & Android

COMPATIBLE WITH:



ALI-AA1
Outdoor Pole Mount Adapter
for ALI-AB1 and ALI-AB2
Brackets



ALI-AB2
Long Wall Mount Bracket



ALI-AA2
Outdoor Corner Mount
Adapter



ALI-AJ5
Round Junction
Box for Domes



ALI-AB1
Short Wall Mount Bracket