

Key Features:

- + 5.0 MP resolution HD video
- + 2560 x 1944 resolution @ 20 fps
- + 2.7 - 13.5 mm lens offers 95.7° to 29.1° field of view
- + Convenient Up the Coax (UTC) Control
- + OSD, 2D DNR & D-WDR
- + IP67 Rated Housing
- + -40°F -140°F operating temperatures



HD **5.0 Megapixel**

5MP HD 130' IR VARIFOCAL BULLET CAMERA

Send HD video over
standard RG59 coax cable

To capture clear and vivid high-definition video, look no further than this Alibi 5.0 Megapixel HD 130' IR bullet security camera. Thanks to its 5.0 MP High-Performance CMOS, with an active imaging pixel array of 2560 (H) x 1944 (V), it produces up to 5.0 MP HD-quality video.

With cutting-edge Full Frame Illumination technology, this camera is able to reduce overexposure of the IR LEDs at the center of the image, increases illuminant efficiency up to 30%, produces LED light in rectangle form to better fit screen size, and captures images up to 130' in the dark without washing out the subject at closer ranges. Together with the True Day/Night feature, this camera is an ideal solution for 24/7 surveillance.

A 2.7 - 13.5 mm wide angle lens provides an 95.7° to 29.1° FOV (Field of View) and enables the camera to cover a large area. Up the Coax (UTC) technology enables you to control the camera's onscreen display (OSD) from your web browser, digital video recorder interface such as the Alibi Central Management System or smart phone app.

Take advantage of HD-TVI's zero latency HD video and long-distance transmission over twisted-pair and coax cable or similar. This means you can keep your existing cables and upgrade your cameras with minimal effort.

The camera has a temperature rating of -40° to 140°F, and for protection from other outdoor elements such as dust and sand, the camera housing is IP67 weather-rated.

What's Included:

- + (1) 5.0 MP HD 130' IR Outdoor Varifocal Bullet Camera
- + (1) Mounting template
- + (1) Mounting hardware
- + (1) Quick start guide



SPECIFICATIONS

Imager Type	CMOS
Color	Yes
Camera Resolution (px)	2560 x 1944
Megapixel	5.0
Day/Night Function	True D/N w/Mechanical Cut Filter
Digital Noise Reduction (DNR)	2D DNR
Electronic Shutter	1/25(1/30) to 1/50,000 sec
IR Array Range (ft)	130
Lux (B/W)	0.0
Lux (Color)	0.01
OSD	Yes
Wide Dynamic	D-WDR
FOV (degrees)	95° (wide) - 29° (telephoto)
Lens Included	Yes
Lens Type	Motorized Varifocal
Focal Length (mm)	2.7 - 13.5
Dimensions	3.33" x 3.62" x 10"
Construction	Plastic and Metal Alloy
Mounting Bracket Included	Yes
Operating Humidity	90% or less (non-condensing)
Operating Temperature (F)	-40° -140°
Product Color	White/Black
Outdoor	Yes
Ingress Protection	IP67
Weight (lb)	1.5
Dual Voltage	Yes
Power (w)	Max 8.9 W
Volts AC	24
Volts DC	12